

IMPACT WRENCH 3/8" MI-12

This TOKU Impact Wrench has an excellent weigth/power ratio. The MI-12 is developed for assembly- and disassembly purposes. The Twin Hammer impactmechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- · Adjustable power, 4 positions
- Exhaust through rubber sealed grip, with silencer


Related products



AC30A-F03E-B Modular FRL Unit



D0605121301





DO611101301

Impact Socket Set 3/8" 13-parts

Related accessories



ATLUB

Air Tool Oil, 1 litre



Specifications

RPM

Brand	Toku
Square Drive	3/8"
Version	R
Bolt capacity (mm)	12

Impact mechanism Twin-Hammer

9500

Torque (Nm) 160

Force adjustment R/L 4 Standen

Airconsumption (I/s) 5,3

Weight (kg) 1,2

Airconnection PT 1/4"
Airpress max. (MPa) 0,63
mm A 150
mm B 24
Hosediameter (mm) 6,5

Safety standard EN ISO 11148-6 Vibration standard EN ISO 28927-2

Vibration value (m/s²) 5,9

Vibration uncertainty (m/s²) 1,08

Sound standard ISO 15744

Sound pressure (dB(A)) 87

Sound power (dB(A)) 98

Sound uncertainty (dB(A)) 3

EAN 8717981000142

