

# 6MM DIE GRINDER IN SET RRG-260RE/SET

RED ROOSTER die grinders are extremely suitable for de-burring applications as well as weld seam finishing and general die grinding applications. The RRG range of die grinders is developed for enhanced productivity, the shaft can be locked by push-button for easy changing of burrs.

**Characteristics:**

- The composite tool cover allows the hand to grip the tool firmly due to the unique ergonomic design.
- The grinders have an adjustable rear exhaust.
- Air inlet with a swivel allowing the tool to be very flexible, especially in difficult access areas.
- When depressed fully the safety lever lays flat against the tool adding extra comfort for the operator.
- The power dial sets the tool performance to the operators choice.

Delivered including an assortment of abrasives



## Specifications

|                                                |                        |
|------------------------------------------------|------------------------|
| <b>Brand</b>                                   | <b>RedRooster</b>      |
| <b>RPM</b>                                     | <b>25000</b>           |
| <b>Airconsumption (l/s)</b>                    | <b>7,5</b>             |
| <b>Weight (kg)</b>                             | <b>0,5</b>             |
| <b>Airconnection</b>                           | <b>PT 1/4"</b>         |
| <b>Airpress max. (MPa)</b>                     | <b>0,63</b>            |
| <b>mm A</b>                                    | <b>176</b>             |
| <b>mm B</b>                                    | <b>41,8</b>            |
| <b>mm C</b>                                    | <b>19</b>              |
| <b>mm D</b>                                    | <b>34,5</b>            |
| <b>mm E</b>                                    | <b>42,7</b>            |
| <b>Hosediameter (mm)</b>                       | <b>10</b>              |
| <b>Collet chuck (mm)</b>                       | <b>6</b>               |
| <b>Power (kW)</b>                              | <b>0,26</b>            |
| <b>Wheel size (mm)</b>                         | <b>35</b>              |
| <b>Safety standard</b>                         | <b>EN ISO 11148-7</b>  |
| <b>Vibration standard</b>                      | <b>EN ISO 28927-12</b> |
| <b>Vibration value (m/s<sup>2</sup>)</b>       | <b>2,5</b>             |
| <b>Vibration uncertainty (m/s<sup>2</sup>)</b> | <b>0,74</b>            |
| <b>Sound standard</b>                          | <b>ISO 15744</b>       |
| <b>Sound pressure (dB(A))</b>                  | <b>83</b>              |
| <b>Sound power (dB(A))</b>                     | <b>94</b>              |
| <b>Sound uncertainty (dB(A))</b>               | <b>3</b>               |
| <b>EAN</b>                                     | <b>8717981406579</b>   |

