

# COMPOSITE IMPACT WRENCH 3/4

## RRI-2500M

This composite impact wrench by RED ROOSTER has an excellent weight/power ratio. The RRI-2500M is developed for assembly- and disassembly applications. The revolutionary Mechoneer impact mechanism gives high energy levels per impact. The Mechoneer impact mechanism combines the hitting strength of a Twin Hammer with the durability advantage of the closed hammer mechanism. On top of that, it is greased fully, which results in low vibration levels and low sound pressure. The tool is suitable for industrial use.  
 Breakloose torque: 2.700 Nm.

### Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Mechoneer Impact mechanism
- Power adjustable, 2 positions forward
- Exhaust silenced, through grip
- Forward/Reverse lever on trigger, for one-hand operation
- 2-Step trigger for controlled rundown

### Related products

-  DO605421001  
Impact Socket Set 3/4" deep 10p
-  AC40A-F04-D  
Modular FRL unit
-  DO605401001  
Socketset 3/4" 10-Parts

### Related accessories

-  DOESR-2  
Ret Ring
-  ATLUB  
Air Tool Oil, 1 litre
-  DOESR-1  
Ret Ring



### Specifications

|                                           |                      |
|-------------------------------------------|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Square Drive                              | 3/4"                 |
| Version                                   | R+H                  |
| Bolt capacity (mm)                        | 24                   |
| Impact mechanism                          | Mechoneer            |
| RPM                                       | 5500                 |
| Torque (Nm)                               | 2000                 |
| Force adjustment                          | L/R 2 Pos.           |
| Airconsumption (l/s)                      | 16                   |
| Weight (kg)                               | 3,5                  |
| Airconnection                             | 3/8"                 |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 187                  |
| mm B                                      | 45                   |
| Hosediameter (mm)                         | 13                   |
| Safety standard                           | EN ISO 11148-6       |
| Max. breakaway torque (Nm)                | 2700                 |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | 7                    |
| Vibration uncertainty (m/s <sup>2</sup> ) | 1,19                 |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 88,4                 |
| Sound power (dB(A))                       | 99,4                 |
| Sound uncertainty (dB(A))                 | 3                    |
| EAN                                       | 8717981400805        |

