



YZ-NP950E

Manual

DE

www.rami-yokota.com



Technische Spezifikationen

Marke	Yokota
Antriebsvierkant	3/8"
Schraubendurchmesser (mm)	8 - 10
Drehzahl (min-1)	2000 - 4800
Drehmoment (Nm)	45 ~ 60
Gewicht ohne Akku (kg)	1,25
mm A	164
mm B	29,5
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,0
Sicherheitsnorm	2014/30/EU, 2011/65/EU, 2015/863 II EN 62481-1 :2015, EN 62481-2-2 :2014, EN 61000-6-2 :2005, EN 61000-6-4 :2007+A1 :2011, EN IEC 6300-0 :2018
Formal Capacity	20 ~ 65
Formal Serie From	0S0001
Vibrationsstandard	EN ISO 28927-2
Vibrationswert (m/s ²)	< 2,5
Vibrationsunsicherheit (m/s ²)	1
Schallstandard	ISO 15744
Schalldruck (dB(A))	79
Schallunsicherheit (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	006
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981415434

www.rami-yokota.com

RAMI YOKOTA BV | DE RUYTERKADE 120 | 1011 AB AMSTERDAM | THE NETHERLANDS
Tel. +31-(0)20-5318800 E-mail info@rami-yokota.com www.rami-yokota.com

