



YZ-NP900E

Manual

NL

www.rami-yokota.com



Technische specificaties

Merk	Yokota
Aandrijfvierkant	3/8"
Boutcapaciteit (mm)	8 - 10
Toerental (min-1)	2000 - 4800
Koppel (Nm)	34 ~ 50
Gewicht zonder accu (kg)	1,20
mm A	164
mm B	29,5
Batterij voltage (Volt)	18
Battery type Li-ion....(Ah)	2,0
Veiligheidsnorm	2014/30/EU, 2011/65/EU, 2015/863 II EN 62481-1 :2015, EN 62481-2-2 :2014, EN 61000-6-2 :2005, EN 61000-6-4 :2007+A1 :2011, EN IEC 6300-0 :2018
Formal Capacity	16 ~ 60
Formal Serie From	0S0001
Vibratiestandaard	EN ISO 28927-2
Vibratiewaarde (m/s ²)	< 2,5
Vibratieonzekerheid (m/s ²)	1
Geluidsstandaard	ISO 15744
Geluidsdruk (dB(A))	78
Geluidsonzekerheid (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	006
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981415441

www.rami-yokota.com

RAMI YOKOTA BV | DE RUYTERKADE 120 | 1011 AB AMSTERDAM | THE NETHERLANDS
Tel. +31-(0)20-5318800 E-mail info@rami-yokota.com www.rami-yokota.com

