



YZ-NP800A

Manual

FR

www.rami-yokota.com



Spécifications techniques

Marque	Yokota
Calibre de vissage (mm)	6 - 8
Vitesse à vide (RPM)	2000 - 4800
Couple (Nm)	15 ~ 30
Poids sans batterie (kg)	1,05
mm A	157
mm B	29,5
Entrainement	1/4" HEX
Batterie voltage (Volt)	18
Batterie type Li-ion....(Ah)	2,0
Norm de sécurité	2014/30/EU, 2011/65/EU, 2015/863 II EN 62481-1 :2015, EN 62481-2-2 :2014, EN 61000-6-2 :2005, EN 61000-6-4 :2007+A1 :2011, EN IEC 6300-0 :2018
Formal Capacity	7 ~ 30
Formal Serie From	0S0077
Norme de vibration	EN ISO 28927-2
Valeur vibratoire (m/s ²)	< 2,5
Incertitude de vibration (m/s ²)	1
Norme sonore	ISO 15744
Pression acoustique (dB(A))	76
Incertitude acoustique (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	006
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981415397

www.rami-yokota.com

RAMI YOKOTA BV | DE RUYTERKADE 120 | 1011 AB AMSTERDAM | THE NETHERLANDS
Tel. +31-(0)20-5318800 E-mail info@rami-yokota.com www.rami-yokota.com

