



YZ-NP600A

Manual

NL

www.rami-yokota.com



Technische specificaties

Merk	Yokota
Boutcapaciteit (mm)	6
Toerental (min-1)	2000- 4800
Koppel (Nm)	7 ~ 18
Gewicht zonder accu (kg)	1,0
mm A	152
mm B	29,5
Aandrijfvierkant / - zeskant	1/4" HEX
Batterij voltage (Volt)	18
Battery type Li-ion....(Ah)	2,0
Veiligheidsnorm	2014/30/EU, 2011/65/EU,2015/863 II EN 62481-1 :2015, EN 62481-2-2 :2014, EN 61000-6-2 :2005, EN 61000-6-4 :2007+A1 :2011, EN IEC 6300-0 :2018
Formal Capacity	7 ~ 20
Formal Serie From	0S0001
Vibratiestandaard	EN ISO 28927-2
Vibratiewaarde (m/s ²)	< 2,5
Vibratieonzekerheid (m/s ²)	1
Geluidsstandaard	ISO 15744
Geluidsdruk (dB(A))	72
Geluidsonzekerheid (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	006
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981415366

www.rami-yokota.com

RAMI YOKOTA BV | DE RUYTERKADE 120 | 1011 AB AMSTERDAM | THE NETHERLANDS
Tel. +31-(0)20-5318800 E-mail info@rami-yokota.com www.rami-yokota.com

