



YZ-NP800A

Manual

DE

www.rami-yokota.com



Technische Spezifikationen

Marke	Yokota
Schraubendurchmesser (mm)	6 - 8
Drehzahl (min-1)	2000 - 4800
Drehmoment (Nm)	15 ~ 30
Gewicht ohne Akku (kg)	1,05
mm A	157
mm B	29,5
Antriebsvierkant/Sechskant	1/4" HEX
Battery voltage (Volt)	18
Battery type Li-ion....(Ah)	2,0
Sicherheitsnorm	2014/30/EU, 2011/65/EU, 2015/863 II EN 62481-1 :2015, EN 62481-2-2 :2014, EN 61000-6-2 :2005, EN 61000-6-4 :2007+A1 :2011, EN IEC 6300-0 :2018
Formal Capacity	7 ~ 30
Formal Serie From	0S0077
Vibrationsstandard	EN ISO 28927-2
Vibrationswert (m/s ²)	< 2,5
Vibrationsunsicherheit (m/s ²)	1
Schallstandard	ISO 15744
Schalldruck (dB(A))	76
Schallunsicherheit (dB(A))	3
Product Group	Impulse Wrenches
Sales Group	006
UNSPSC number	27131501
Eclass number	21061206
EAN	8717981415397

www.rami-yokota.com

RAMI YOKOTA BV | DE RUYTERKADE 120 | 1011 AB AMSTERDAM | THE NETHERLANDS
Tel. +31-(0)20-5318800 E-mail info@rami-yokota.com www.rami-yokota.com

