

CONTROLLED PRECISION IN TIGHTENING

IMPULSE WRENCH 1/2" YLA140E

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air.

Related products



TW-3 Spring balancer 1,0-3,0 kg

Related accessories



Tool Holder, diameter 73mm **Rubber protection cover YLA140**



Specifications

Brand	Yokota
Bolt capacity (mm)	14
RPM	6000
Torque (Nm)	100 - 160
Weight (kg)	2,2
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
Airconsumption fullload (I/s)	13,0
mm A	190
mm B	30
Hosediameter (mm)	9,5
Square Drive / Hexagon	1/2"
Safety standard	EN ISO 11148-6
Air consumption no load (I/s)	18,9
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	4,7
Vibration uncertainty (m/s²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	83
Sound power (dB(A))	94
Sound uncertainty (dB(A))	3
EAN	8717981099146

