

COMPOSITE IMPACT WRENCH 1/2" MI-17C

This TOKU composite impact wrench has an excellent weight/power ratio. The MI-17C is developed for assembly- and disassembly purposes. The Twin Hammer impact mechanism has a high energy level at each impact and thus suitable for heavy duty application. The energy is brought directly to the drive shaft for maximum power and minimal maintenance. This tool is suitable for industrial use. Breakloose torque: 1.600 Nm.

Characteristics:

- Ergonomic design, well balanced
- Compact and lightweight
- Clutch: Twin Hammer
- Adjustable power, 3 positions.

Related products

-  **DO605201003**
Socketset 1/2" 10-Parts
-  **DO605222601**
Impact Socket Set 1/2" deep 26 parts
-  **DO691121301**
Impact Socket Set 1/2" & bits
-  **AC30A-F03E-B**
Modular FRL Unit
-  **DO69523108**
Socketset 1/2" deep 10-Parts
-  **DO605202602**
Impact Socket Set 1/2" - 26 parts
-  **DO652260701**
Impact Socket Set 1/2" triple square

Related accessories

-  **13-08-09-054**
Hanger
-  **ATLUB**
Air Tool Oil, 1 litre



Specifications

Brand	Toku
Square Drive	1/2"
Version	R
Bolt capacity (mm)	16
Impact mechanism	Twin-Hammer
RPM	8800
Torque (Nm)	815
Force adjustment	R 3 / L 2
Airconsumption (l/s)	13,3
Weight (kg)	1,84
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	181
mm B	31
Hosediameter (mm)	10
Safety standard	EN ISO 11148-6
Max. breakaway torque (Nm)	1600
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	5,7
Vibration uncertainty (m/s ²)	1,06
Sound standard	ISO 15744
Sound pressure (dB(A))	93
Sound power (dB(A))	104
Sound uncertainty (dB(A))	3
EAN	8717981369522

