

CONTROLLED PRECISION IN TIGHTENING

## **POKA YOKE IMPULSE WRENCH 1/2"** YLA120E-JQ

ľ

Yokota impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor. Extremely low weight and adapted for use with non-lubricated air. Exclusively for use with YTC-3 Poka Yoke controller.

## **Related products**



YTC-3\* Poka Yoke+ Controller

TW-3 Spring balancer 1,0-3,0 kg

## **Related accessories**

61022-TH003 Tool Holder, diameter 58mm 0345-0029-00-00 Rubber Tool Cover YLA120E

Specifications	
Brand	Yokota
Bolt capacity (mm)	12
RPM	6600
Torque (Nm)	80 - 130
Airconsumption (I/s)	10,0
Weight (kg)	1,8
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	172
mm B	28
Hosediameter (mm)	10
Square Drive / Hexagon	1/2"
Safety standard	EN ISO 11148-6
Air consumption no load (I/s)	15,6
Vibration standard	EN ISO 28927-2
Vibration value (m/s²)	3,9
Vibration uncertainty (m/s²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	81
Sound power (dB(A))	92
Sound uncertainty (dB(A))	3
EAN	8717981014446

