

IMPACT WRENCH 1"

MI-38ESR

This industrial impact wrench by Toku has proven capabilities. The MI-38ESR is developed for tightening and untightening applications. The Twin Hammer mechanism can virtually not be damaged hence applicable for heavy duty applications. The energy is directly converted to the anvil for maximum power and minimal maintenance. The tool is especially suitable for use in the tire industry.

Characteristics:

- * Ergonomic design, well balanced
- * Compact and lightweight
- * Power adjustable, 4 positions

Related products



DO0100-1-007

Socketset Long 1" 7-Parts

Related accessories



DOESR-3

Ret Ring



Specifications

Brand	Toku
Square Drive	1"
Version	R+H
Bolt capacity (mm)	36
Impact mechanism	Twin-Hammer
RPM	3700
Torque (Nm)	1850
Force adjustment	R/L 4 Standen
Airconsumption (l/s)	11,6
Weight (kg)	7,7
Airconnection	PT 1/2"
Airpress max. (MPa)	0,63
mm A	337
mm B	50
Hosediameter (mm)	13
Safety standard	EN ISO 11148-6
Vibration standard	EN ISO 28927-2
Vibration value (m/s ²)	12,2
Vibration uncertainty (m/s ²)	1,70
Sound standard	ISO 15744
Sound pressure (dB(A))	96
Sound power (dB(A))	107
Sound uncertainty (dB(A))	3
EAN	8717981038572

