

VERTICAL GRINDER 180MMX22MM

7VC-8500FS

This vertical grinder of Yokota is used in industrial applications and shipyards. The grinder has an integrated speed-regulator for a maximum of safety and the optimal performance in material removal.

Characteristics:

- * Ergonomic design, well balanced
- * The air-exhaust is silenced
- * Safety start lever

Related accessories

- | | |
|---|--|
|  | 1508-0655-00-00
Outer Wheel Screw |
|  | 9310-3006-00-99
Rubber Pad (178) With Flange |
|  | 1508-0653-00-03
Inner Flange |
|  | 8100-5001-00-00
Twin Wrench |
|  | 8100-4003-00-01
Hook Wrench |
|  | 9310-3006-00-00
Rubber pad G-70/7VC-6500/7VC-8500 |
|  | 1508-0654-05-05
Pad Flange |
|  | 1508-0654-00-01
Outer Flange |
|  | 1508-0653-01-02
Inner Flange |
|  | 1422-0653-00-99
Inner Flange |
|  | 8100-5002-00-00
Twin Wrench G70EF/7VC-6500/7VC-8500 |
|  | 1508-0654-00-02
Outer Flange |



Specifications

Brand	Yokota
RPM	8500
Airconsumption (l/s)	23,0
Weight (kg)	4,1
Sound level (dB(A))	83
Airconnection	PT 3/8"
Airpress max. (MPa)	0,63
mm A	195
mm B	180
mm C	180
mm D	165
Hosediameter (mm)	13
Spindle	5/8"
Power (kW)	1,74
Vibration level (m/s ²)	2,1
Wheel size (mm)	180 x 6 x 22
Safety standard	EN ISO 11148-7
EAN	8717981000043

