

AUTO-SHUT-OFF SCREWDRIVER RRI-SA50322

The RED ROOSTER Shut-Off screwdrivers have a large torque-range, are highly accurate and have a low vibration level. Very ergonomic design and low noise level. The special design of the clutch combines low reaction forces with a high repeatability of the torque. This air tool is designed for the assembly industry, where threaded fasteners are used.

Characteristics:

- New angled body-design with soft grip
- Reversible
- Rear-exhaust, silenced
- ergonomic grip, lever start
- easily adjustable

Related products



TW-3

Spring balancer 1,0-3,0 kg

Related accessories



00-4507

Torque Adjust Key RRI screwdriver



Specifications

Brand	RedRoosterIndustrial
Bolt capacity (mm)	6
RPM	320
Torque (Nm)	14,0 - 22,0
Airconsumption (I/s)	11
Weight (kg)	1,81
Hexagon	1/4"
Sound level (dB(A))	74
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	369
mm B	38
mm C	14
mm D	16
mm E	16
Hosediameter (mm)	6,5
Execution	Angle
Vibration level (m/s²)	< 2,5
Safety standard	EN ISO 11148-6
FAN	8717981414949

