

# IMPULSE WRENCH 3/8 SHUT-OFF YLTX60E

YOKOTA impulse wrenches are widely used for tightening jobs in the assembly industry, where accurate torque tolerances are necessary. Impulse tools are light, powerful, small and very importantly, have no kick-back. Pistol model with double chamber airmotor and auto shut-off. No-lube airmotor.

## Related products



**TW-3**

Spring balancer 1,0-3,0 kg

## Related accessories

0371-0029-00-00

Rubber protection cover YLT50 YLT60



## Specifications

|                                           |                |
|-------------------------------------------|----------------|
| Brand                                     | Yokota         |
| Bolt capacity (mm)                        | 6              |
| RPM                                       | 5300           |
| Torque (Nm)                               | 7 - 15,5       |
| Airconsumption (l/s)                      | 5,5            |
| Weight (kg)                               | 0,95           |
| Airconnection                             | PT 1/4"        |
| Airpress max. (MPa)                       | 0,63           |
| mm A                                      | 164            |
| mm B                                      | 22,5           |
| Hosediameter (mm)                         | 6,5            |
| Square Drive / Hexagon                    | 3/8"           |
| Safety standard                           | EN ISO 11148-6 |
| Air consumption no load (l/s)             | 5,6            |
| Vibration standard                        | EN ISO 28927-2 |
| Vibration value (m/s <sup>2</sup> )       | < 2,5          |
| Vibration uncertainty (m/s <sup>2</sup> ) | 1              |
| Sound standard                            | ISO 15744      |
| Sound pressure (dB(A))                    | 72             |
| Sound uncertainty (dB(A))                 | 3              |
| EAN                                       | 8717981356225  |

