

DOWEL PIN PULLER

YDP-13

The Yokota dowel pin puller is used in matrix, casting and press-moulding industries, for setting and removing dowel pins in moulds or presses. The dowel pin puller is an easily operated air tool and can simplify the pulling or hammering operation of the threaded dowel pins, saving time and improving working efficiency.

Related accessories

6502-0022-00-07	Hanger Bolt M8X150L
6502-0022-00-08	Hanger Bolt M8X200L
6502-0022-00-06	Hanger Bolt M8X100L
6502-0022-00-12	Hanger Bolt M6X200L
6502-0022-00-14	Hanger Bolt M5X100L
6502-0022-00-10	Hanger Bolt M6X100L
6502-0022-00-19	Hanger Bolt M4X150L
6502-0022-00-11	Hanger Bolt M6X150L
6502-0022-00-13	Hanger Bolt M5X 50L
6502-0022-00-17	Hanger Bolt M4X 50L
6502-0022-00-18	Hanger Bolt M4X100L
6502-0022-00-09	Hanger Bolt M6X 50L
6502-0022-00-16	Hanger Bolt M5X200L
6502-0022-00-20	Hanger Bolt M4X200L
6502-0022-00-15	Hanger Bolt M5X150L



Specifications

Brand	Yokota
Airconsumption (l/s)	3,3
Weight (kg)	1,35
Capacity pin (mm)	13
Airconnection	PT 1/4"
Airpress max. (MPa)	0,63
mm A	162
mm B	75
Stroke (mm)	30 x 25
Strokes per minute	5000
Hosediameter (mm)	6,5
Safety standard	EN ISO 11148-4
Vibration standard	EN ISO 28927-9
Vibration value (m/s ²)	5,1
Vibration uncertainty (m/s ²)	1
Sound standard	ISO 15744
Sound pressure (dB(A))	94
Sound power (dB(A))	105
Sound uncertainty (dB(A))	3
EAN	8717981141418

