

# ANGLE GRINDER, 125 X 22MM RRG-2155

The improved RED ROOSTER compact angle grinder: lighter and 60% more powerful.

## Characteristics:

- ideal for cutting and grinding
- vibration-reduced dead-handle suitable for both left-hand and right-hand users
- metrical spindle allows use of widely used abrasives
- spindle-lock for quick change of abrasives
- protective cover can easily be adjusted

## Related products



**AC30A-F03E-B**  
Modular FRL Unit

## Related accessories



**2400-046-11**  
Dead Handle Vibration Red.

**9310-3011-00-00**  
Rubber pad 125x22



**QN-M14**  
Quick Nut M14X2.0P



**EH-6191SUB**  
Silencer Kit Complete RRG-2155



**ATLUB**  
Air Tool Oil, 1 litre



## Specifications

|                                                |                        |
|------------------------------------------------|------------------------|
| <b>Brand</b>                                   | RedRooster             |
| <b>RPM</b>                                     | 12.000                 |
| <b>Airconsumption (l/s)</b>                    | 17,4                   |
| <b>Weight (kg)</b>                             | 1,9                    |
| <b>Airconnection</b>                           | PT 3/8"                |
| <b>Airpress max. (MPa)</b>                     | 0,63                   |
| <b>mm A</b>                                    | 253                    |
| <b>mm B</b>                                    | 95                     |
| <b>mm C</b>                                    | 35                     |
| <b>mm D</b>                                    | 60                     |
| <b>Hosediameter (mm)</b>                       | 13                     |
| <b>Spindle</b>                                 | M14 x 2                |
| <b>Power (kW)</b>                              | 1,04                   |
| <b>Wheel size (mm)</b>                         | 125 x (0,8 - 7) x 22,2 |
| <b>Safety standard</b>                         | EN ISO 11148-7         |
| <b>Vibration standard</b>                      | EN ISO 28927-1         |
| <b>Vibration value (m/s<sup>2</sup>)</b>       | 6,6                    |
| <b>Vibration uncertainty (m/s<sup>2</sup>)</b> | 1,3                    |
| <b>Sound standard</b>                          | ISO 15744              |
| <b>Sound pressure (dB(A))</b>                  | 88                     |
| <b>Sound power (dB(A))</b>                     | 99                     |
| <b>Sound uncertainty (dB(A))</b>               | 3                      |
| <b>EAN</b>                                     | 8717981364688          |

