

# IMPULSE WRENCH 1/4 HEX SHUT-OFF RRI-70AT

The RED ROOSTER Impulse wrenches are handheld tools made for assembly with threaded fasteners. Impulse wrenches increase productivity. Typically meant for use in: Production of agricultural machinery, production of pumps, motors, bikes and any other serial production. The tool has a wide body air motor. Torque level adjustable in the impulse mechanism.

#### Characteristics:

- Lightweight
- Free of reaction forces
- Low noise and vibration levels
- Powerful and fast
- High repeatability of the torque level
- Pistol model
- Auto shut off function

#### Related products



**TW-3**  
Spring balancer 1,0-3,0 kg

#### Related accessories

01-0505Y0  
standard accessories kit  
I70-109-A05  
Protection Cover RRI-70(A/T)  
61022-TH003  
Tool Holder, diameter 58mm



#### Specifications

|   |                      |
|---|----------------------|
| Brand                                     | RedRoosterIndustrial |
| Bolt capacity (mm)                        | 10                   |
| RPM                                       | 7200                 |
| Torque (Nm)                               | 32 - 47              |
| Airconsumption (l/s)                      | 7,0                  |
| Weight (kg)                               | 1,35                 |
| Airconnection                             | PT 1/4"              |
| Airpress max. (MPa)                       | 0,63                 |
| mm A                                      | 194                  |
| mm B                                      | 172                  |
| Hosediameter (mm)                         | 8                    |
| Square Drive / Hexagon                    | 1/4"                 |
| Safety standard                           | EN ISO 11148-6       |
| Vibration standard                        | EN ISO 28927-2       |
| Vibration value (m/s <sup>2</sup> )       | 4                    |
| Vibration uncertainty (m/s <sup>2</sup> ) | 0,89                 |
| Sound standard                            | ISO 15744            |
| Sound pressure (dB(A))                    | 76,3                 |
| Sound uncertainty (dB(A))                 | 3                    |
| EAN                                       | 8717981205592        |

