

AIR CHAIN HOIST 6000 KG TMH-6000LFP2E

The new RED ROOSTER LF series of lubrication free hoists is the latest addition in a line of new models within the Red Rooster air hoist range. The oil free operation allows the hoist to run whilst preventing any oil being exhausted into the atmosphere, making the units ideal for use where a clean environment is a requirement. These new air hoists are suitable for food, chemical, pharmaceutical and painting industries.




CHARACTERISTICS:


- Precise variable speed control
- Optimum control of the load
- Robust and reliable
- Mechanical end stop
- High quality RUD hoist chain
- Full load supporting eye for safe installation
- Standard delivered including ATEX zone 2 certificate

OPTIONS:

- Paint systems for C5 Marine
- Zone 1 ATEX certification
- Chain collectors
- Hook or clevis options
- Air supply systems and valves

Related products

- 
AW60-F10DE-B
 Filter/Regulator
- 
42-02-28-VRD
 Pendant Valve Assy TCR/TMH
- 
13X36
 Chain EN 818-7



Specifications

| | |
|----------------------------------|---------------|
| Brand | RedRooster |
| Weight (kg) | 124 |
| Number of chain falls | 2 |
| Lowering speed full load (m/min) | 2,8 |
| Lowering speed 0-load (m/min) | 1,6 |
| Lifting speed full load (m/min) | 1,6 |
| Lifting speed 0-load (m/min) | 3,2 |
| Chain weight (kg/m) | 3,8 |
| Chain (mm) | 13 x 36 |
| Airconnection | 1" BSPT |
| Airconsumption fullload (l/s) | 51 |
| mm A | 742 |
| mm B | 371 |
| mm C | 245 |
| mm D | 126 |
| mm E | 265 |
| mm F | 311 |
| mm H | 65 |
| mm I | 42 |
| Hosediameter (mm) | 19 |
| SMC Airtreatment unit | AW60-F10DE-B |
| Workingpressure (MPa) | 0,63 |
| Capacity (kg) | 6000 |
| Airconnection exhaust | 1" |
| EAN | 8717981389322 |